



X⁴ 7300



**EXCEPTIONAL TEMPERATURE CONTROL
WITH A NEW DIMENSION IN
PERFORMANCE AND EFFICIENCY.**



Condenser Dimensions

76.4" x 25.7" x 22.8"
(1,940 x 2,176 x 579 mm)

Evaporator Dimensions

66.3" x 45.2" x 8.2"
(1,681 x 1,149 x 280 mm)

Body Opening

65.8" x 46.0"
(1,696 x 1,168 mm)

Approximate Weight

1,685 lb. (765 kg)
mounting brackets

Cooling/Temperature Capacity

Ambient at 86°F (30°C)

Evaporator Return Air Temp.	High Speed Diesel Operation	
	BTU/hr	Watts
32°F (0°C)	71,130	20,850
-4°F (-20°C)	38,370	11,250

Evaporator Airflow:

Applied system performance:
3,050 cfm (5,180 m³/hr)

The X4™ Series. Built upon the proven X2™ platform, the X4 7300 is higher as the new industry standard for refrigeration performance and efficiency.

Ultra high capacity. The model 7300 establishes the benchmark for extreme performance. It delivers fast pulldown, precise temperature control and peace of mind for the most demanding applications.

Ultra high efficiency. EcoFORWARD™ technologies deliver significant fuel savings as well as higher performance, lower operating costs and compliance with 2013 EPA emissions regulations.

Proven reliability. The enhanced platform now includes proven high efficiency components from our Vector™ series and an industry-leading warranty for dependability and peace of mind.

APX™ control system. The modular APX system combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

Lower cost of ownership. Combining innovative engineering with a straightforward, practical design means less fuel consumption, reduced engine run hours, and lower maintenance costs.

Standard Features include:

- Tier 4 Final V2203L smart diesel engine
- 4 cylinder 2.2 liter direct injection
- 24.8 hp (18.5kW) at 1,800 RPM high speed
- CAN bus electronic interface
- 15 qt. (14.2 liter) oil capacity
- High power 70 amp alternator
- ESI™ (Extended Service Interval) package
- 3,000 hour service interval
- Multistage, synthetic media oil filter
- Water separating fuel filter
- Heavy duty, low noise dry air cleaner
- Extended life coolant
- 05G 41CFM compressor
- 40 in³ displacement
- 6 cylinders
- Refrigerant R-404A, 15.0 lb (7.3 kg)
- UltraFresh 3™ temperature control
- TRU-DEMAND™ high energy efficiency
- Electronic expansion valve
- Electronic suction modulation
- Compressor unloaders
- Brazed plate heat exchanger
- Automatic start/stop fuel saver
- Automatic hot gas heating system
- APX™ Control System
- IntelliSet™ with ProductShield™
- DataLink™ data recorder
- Information dashboard
- Multilingual graphical display
- Pretrip and Virtual Tech diagnostics
- Integrated USB port

Standard Features (continued):

- High efficiency microchannel condenser
- V-Force™ vortex suppression fan
- TurboAir™ evaporator management
- Durashell™ 2 composite doors
- Single latch release
- Installation package
- Screw-post battery terminals

Accessories and Options:

- DataTrak™ remote communications
- AutoFresh™ Function air exchange
- APX Remote Control Panel
- Remote aluminum fuel tanks:
 - 120L/200L
 - 26-gal/44-gal

